



Antique Brass MLWL238ANTBRS





| MATERIAL | Brass |
|--------------------------|--|
| HEIGHT | 17-22cm 6.69-8.66" |
| WIDTH DIAMETER | 16cm 6.3" |
| LENGTH PROJECTION | 24-34cm 9.45-13.39" |
| WEIGHT | 0.9KG 1.98lbs |
| LAMPHOLDER | E27 x 1 |
| MAX WATTAGE | 40W x 1 |
| VOLTAGE | 220/240v |
| IP RATING | 20 |
| CLASS PROTECTION | I |
| SHADE | |
| FLEX BAR CHAIN LENGT | n/a |
| CABLE TYPE | MLCA047 2 Core Round Brown Braid PVC |

Fixing Bracket MLWB03 | Antique Brass





Product Notes:

1) Lamps not included with lightfixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.)


Products wired to UL standards will operate at 110/120vwith the appropriate lampholders.






Antique Silver MLWL238ANTSLV





| MATERIAL | Brass |
|--------------------------|--|
| HEIGHT | 17-22cm 6.69-8.66" |
| WIDTH DIAMETER | 16cm 6.3" |
| LENGTH PROJECTION | 24-34cm 9.45-13.39" |
| WEIGHT | 0.9KG 1.98lbs |
| LAMPHOLDER | E27 x 1 |
| MAX WATTAGE | 40W x 1 |
| VOLTAGE | 220/240v |
| IP RATING | 20 |
| CLASS PROTECTION | ı |
| SHADE | |
| FLEX BAR CHAIN LENGT | n/a |
| CABLE TYPE | MLCA028 2 Core Round Black Braid PVC |

Fixing Bracket MLWB03 | Antique Silver





Product Notes:

1) Lamps not included with lightfixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.)

Products wired to UL standards will operate at 110/120vwith the appropriate lampholders.






MLWL238POLBRS


Polished Brass





| MATERIAL | Brass |
|--------------------------|--|
| HEIGHT | 17-22cm 6.69-8.66" |
| WIDTH DIAMETER | 16cm 6.3" |
| LENGTH PROJECTION | 24-34cm 9.45-13.39" |
| WEIGHT | 0.9KG 1.98lbs |
| LAMPHOLDER | E27 x 1 |
| MAX WATTAGE | 40W x 1 |
| VOLTAGE | 220/240v |
| IP RATING | 20 |
| CLASS PROTECTION | ı |
| SHADE | |
| FLEX BAR CHAIN LENGT | n/a |
| CABLE TYPE | MLCA028 2 Core Round Black Braid PVC |

Fixing Bracket MLWB03 | Polished Brass






I) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120 with the appropriate lampholders.






MLWL238SATBRS Satin Brass





| MATERIAL | Brass |
|--------------------------|--|
| HEIGHT | 17-22cm 6.69-8.66" |
| WIDTH DIAMETER | 16cm 6.3" |
| LENGTH PROJECTION | 24-34cm 9.45-13.39" |
| WEIGHT | 0.9KG 1.98lbs |
| LAMPHOLDER | E27 x 1 |
| MAX WATTAGE | 40W x 1 |
| VOLTAGE | 220/240v |
| IP RATING | 20 |
| CLASS PROTECTION | ı |
| SHADE | - |
| FLEX BAR CHAIN LENGT | n/a |
| CABLE TYPE | MLCA028 2 Core Round Black Braid PVC |

Fixing Bracket MLWB03 | Satin Brass





I) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120 with the appropriate lampholders.

