mullan

DOON Pendant

MLP424BLK Black







| MATERIAL | Brass Porcelain | Fixii |
|--------------------------|--|-------|
| HEIGHT | 9.5cm 3.74'' | |
| WIDTH DIAMETER | 16cm 6.3'' | |
| LENGTH PROJECTION | n/a | |
| WEIGHT | 1.12KG 2.47lbs | |
| LAMPHOLDER | E27 or E26 | |
| MAX WATTAGE | 60W x 1 | |
| VOLTAGE | 220/240v or 110/120v | |
| IP RATING | 20 | |
| CLASS PROTECTION | I | |
| SHADE | - | |
| FLEX BAR CHAIN LENGT | 100cm 40" | |
| CABLE TYPE | MLCA028 2 Core Round Black Braid PVC | |

ting Bracket MLWB03 | Black

r UL wired lights, fixing bracket may differ 8cm







Product Notes: Product Notes: 1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



mullan

DOON Pendant

MLP424WTE White







| MATERIAL | Brass Porcelain |
|--------------------------|--|
| HEIGHT | 9.5cm 3.74'' |
| WIDTH DIAMETER | 16cm 6.3'' |
| LENGTH PROJECTION | n/a |
| WEIGHT | 0.42KG 0.93lbs |
| LAMPHOLDER | E27 or E26 |
| MAX WATTAGE | 60W x 1 |
| VOLTAGE | 220/240v or 110/120v |
| IP RATING | 20 |
| CLASS PROTECTION | Ι |
| SHADE | - |
| FLEX BAR CHAIN LENGT | 100cm 40" |
| CABLE TYPE | MLCA068 3 Core Round White Braid PVC |

Fixing Bracket MLWB03 | White

*For UL wired lights, fixing bracket may differ







Product Notes: 1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.

