



| | | | |
|---------------------------|--------------------------------------------|----------------|---|
| MATERIAL | Steel Brass | FIXING BRACKET | - |
| HEIGHT | 46cm 18.11" | | |
| WIDTH DIAMETER | 16cm 6.3" | | |
| LENGTH PROJECTION | 31cm 12.2" | | |
| WEIGHT | 2.2kg 4.85lb | | |
| LAMPHOLDER | E27 | | |
| MAX WATTAGE | 25W | | |
| VOLTAGE | 220/240v | | |
| IP RATING | IP20 | | |
| CLASS PROTECTION | 2 | | |
| SHADE | - | | |
| FLEX BAR CHAIN LENGTH | 150cm 60" | | |
| CABLE TYPE | MLCA028 2 Core Round Black Braid PVC | | |



Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.





| | |
|--------------------------|--------------------------------------------|
| MATERIAL | Steel Brass |
| HEIGHT | 46cm 18.11" |
| WIDTH DIAMETER | 16cm 6.3" |
| LENGTH PROJECTION | 31cm 12.2" |
| WEIGHT | 2.2kg 4.85lb |
| LAMPHOLDER | E27 |
| MAX WATTAGE | 25W |
| VOLTAGE | 220/240v |
| IP RATING | IP20 |
| CLASS PROTECTION | 2 |
| SHADE | - |
| FLEX BAR CHAIN LENGT | 150cm 60" |
| CABLE TYPE | MLCA070 2 Core Round White Braid PVC |

FIXING BRACKE -



Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.

