




MLP023PCBLK Black



| MATERIAL | Brass Auminium | I |
|--------------------------|------------------|---|
| HEIGHT | 46cm 18.11" | |
| WIDTH DIAMETER | 41.5cm 16.34" | |
| LENGTH PROJECTION | n/a | |
| WEIGHT | 1.02KG 2.25lbs | |
| LAMPHOLDER | E27 x 1 | |
| MAX WATTAGE | 40W x 1 | |
| VOLTAGE | 220/240v | |
| IP RATING | 20 | |
| CLASS PROTECTION | I | |
| SHADE | | |
| FLEX BAR CHAIN LENGT | 100cm 40" | |
| CABLE TYPE | MLCA009 | |

Fixing Bracket MLROSE05HOOK | Black




Product Notes: 1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.





MLP023PCBRZ Bronze





| MATERIAL | Brass Aluminium |
|--------------------------|-------------------------------------|
| HEIGHT | 46cm 18.11" |
| WIDTH DIAMETER | 41.5cm 16.34" |
| LENGTH PROJECTION | n/a |
| WEIGHT | 1.02KG 2.25lbs |
| LAMPHOLDER | E27 x 1 |
| MAX WATTAGE | 40W x 1 |
| VOLTAGE | 220/240v |
| IP RATING | 20 |
| CLASS PROTECTION | 1 |
| SHADE | |
| FLEX BAR CHAIN LENGT | 100cm 40" |
| CABLE TYPE | MLCA010 2 Core Flat Brown PVC |

Fixing Bracket MLROSE05HOOK | Bronze



Product Notes: 1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.




www.mullanlighting.com



MLP023PCMBK Matt Black





| MATERIAL | Brass Aluminium | I |
|--------------------------|-------------------|---|
| HEIGHT | 46cm 18.11" | |
| WIDTH DIAMETER | 41.5cm 16.34" | |
| LENGTH PROJECTION | n/a | |
| WEIGHT | 1.02KG 2.25lbs | |
| LAMPHOLDER | E27 x 1 | |
| MAX WATTAGE | 40W x 1 | |
| VOLTAGE | 220/240v | |
| IP RATING | 20 | |
| CLASS PROTECTION | 1 | |
| SHADE | - | |
| FLEX BAR CHAIN LENGT | 100cm 40" | |
| CABLE TYPE | MLCA009 | |

Fixing Bracket MLROSE05HOOK | Matt Black



Product Notes: 1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.





MLP023PCWTE White



| MATERIAL | Brass Aluminium |
|--------------------------|-------------------------------------|
| HEIGHT | 46cm 18.11" |
| WIDTH DIAMETER | 41.5cm 16.34" |
| LENGTH PROJECTION | n/a |
| WEIGHT | 1.02KG 2.25lbs |
| LAMPHOLDER | E27 x 1 |
| MAX WATTAGE | 40W x 1 |
| VOLTAGE | 220/240v |
| IP RATING | 20 |
| CLASS PROTECTION | 1 |
| SHADE | |
| FLEX BAR CHAIN LENGT | 100cm 40" |
| CABLE TYPE | MLCA010 2 Core Flat Brown PVC |

Fixing Bracket MLROSE05HOOK | White



Product Notes: 1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: http://www.mullanlighting.com/terms for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.

