


MLCMWL045ANTBRS **Antique Brass**



MATERIAL	Brass Ceramic
HEIGHT	28cm 11.02"
WIDTH DIAMETER	28cm 11.02"
LENGTH PROJECTION	10cm 3.94"
WEIGHT	1.3KG 2.87lbs
LAMP HOLDER	E27 or E26 *
MAX WATTAGE	40W x 1
VOLTAGE	220/240v or 110/120v *
IP RATING	20
CLASS PROTECTION	I
SHADE CODE	MLCS077
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB17

* Fixing bracket may differ for UL wired products.












Antique Silver MLCMWL045ANTSLV



MATERIAL	Brass Ceramic
HEIGHT	28cm 11.02"
WIDTH DIAMETER	28cm 11.02"
LENGTH PROJECTION	10cm 3.94"
WEIGHT	1.3KG 2.87lbs
LAMP HOLDER	E27 or E26 *
MAX WATTAGE	40W x 1
VOLTAGE	220/240v or 110/120v *
IP RATING	20
CLASS PROTECTION	I
SHADE CODE	MLCS077
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB17

* Fixing bracket may differ for UL wired products.












MLCMWL045PCMBK Matt Black



MATERIAL	Brass Ceramic
HEIGHT	28cm 11.02"
WIDTH DIAMETER	28cm 11.02"
LENGTH PROJECTION	10cm 3.94"
WEIGHT	1.3KG 2.87lbs
LAMP HOLDER	E27 or E26 *
MAX WATTAGE	40W x 1
VOLTAGE	220/240v or 110/120v*
IP RATING	20
CLASS PROTECTION	ı
SHADE CODE	MLCS077
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB17

* Fixing bracket may differ for UL wired products.












MLCMWL045POLBRS **Polished Brass**



MATERIAL	Brass Ceramic
HEIGHT	28cm 11.02"
WIDTH DIAMETER	28cm 11.02"
LENGTH PROJECTION	10cm 3.94"
WEIGHT	1.3KG 2.87lbs
LAMP HOLDER	E27 or E26 *
MAX WATTAGE	40W x 1
VOLTAGE	220/240v or 110/120v *
IP RATING	20
CLASS PROTECTION	I
SHADE CODE	MLCS077
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB17

* Fixing bracket may differ for UL wired products.











MLCMWL045SATBRS Satin Brass



MATERIAL	Brass Ceramic
HEIGHT	28cm 11.02"
WIDTH DIAMETER	28cm 11.02"
LENGTH PROJECTION	10cm 3.94"
WEIGHT	1.3KG 2.87lbs
LAMP HOLDER	E27 or E26 *
MAX WATTAGE	40W x 1
VOLTAGE	220/240v or 110/120v *
IP RATING	20
CLASS PROTECTION	I
SHADE CODE	MLCS077
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB17

* Fixing bracket may differ for UL wired products.

