

WADE

MLOSL006ANTBRS

Antique Brass





MATERIAL	Brass Glass
HEIGHT	15.2cm 5.98"
WIDTH DIAMETER	12.7cm 5"
LENGTH PROJECTION	9cm 3.54"
WEIGHT	0.85KG 1.87lbs
LAMP HOLDER	GU10
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v or 110/120v*
IP RATING	54
CLASS PROTECTION	ı
SHADE CODE	
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	

Fixing Bracket

* Fixing bracket may differ for UL wired products.



Product Notes:

1) Bulbs not included. 2) Dimensions do not include bulbs. 3) All products are individually made-to-order and therefore may differ slightly within manufacturing tolerances. 4) Cable / chain can be shortened during installation. Longer cable / chain lengths available on request. 5) Additional colour finishes may be available on request. 6) UL wired products operate at 110/120 with the appropriate lamp holder. 7) Twisted cable is not available for UL wired products. Round cable in black or brown only is supplied instead. 8) Refer to our website for a full list of terms and conditions.





WADE

MLOSL006PCMBK

Matt Black





MATERIAL	Brass Glass Steel
HEIGHT	15.2cm 5.98"
WIDTH DIAMETER	12.7cm 5"
LENGTH PROJECTION	9cm 3.54"
WEIGHT	0.85KG 1.87lbs
LAMP HOLDER	GU10
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v or 110/120v *
IP RATING	54
CLASS PROTECTION	I
SHADE CODE	
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	

Fixing Bracket

* Fixing bracket may differ for UL wired products.









WADE

MLOSL006RAWBRS

Raw Brass





MATERIAL	Brass Glass
HEIGHT	15.2cm 5.98"
WIDTH DIAMETER	12.7cm 5"
LENGTH PROJECTION	9cm 3.54"
WEIGHT	0.85KG 1.87lbs
LAMP HOLDER	GU10
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v or 110/120v*
IP RATING	54
CLASS PROTECTION	I
SHADE CODE	
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	

Fixing Bracket

* Fixing bracket may differ for UL wired products.



Product Notes:

1) Bulbs not included. 2) Dimensions do not include bulbs. 3) All products are individually made-to-order and therefore may differ slightly within manufacturing tolerances. 4) Cable / chain can be shortened during installation. Longer cable / chain lengths available on request. 5) Additional colour finishes may be available on request. 6) UL wired products operate at 110/120 with the appropriate lamp holder. 7) Twisted cable is not available for UL wired products. Round cable in black or brown only is supplied instead. 8) Refer to our website for a full list of terms and conditions.

