




MATERIAL	Brass Glass	Fixing Bracket MLWB07
HEIGHT	40cm 15.75"	
WIDTH DIAMETER	11cm 4.33"	
LENGTH PROJECTION	8cm 3.15"	
WEIGHT	0.65KG	
LAMPHOLDER	G9 x 1	
MAX WATTAGE	6.5W x 1	
VOLTAGE	220/240v	
IP RATING	44	
CLASS PROTECTION	I	
SHADE	GL192	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	



Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Glass
HEIGHT	40cm 15.75"
WIDTH DIAMETER	11cm 4.33"
LENGTH PROJECTION	8cm 3.15"
WEIGHT	0.65KG
LAMPHOLDER	G9 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	I
SHADE	GL192
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB07



Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Glass
HEIGHT	40cm 15.75"
WIDTH DIAMETER	11cm 4.33"
LENGTH PROJECTION	8cm 3.15"
WEIGHT	0.65KG
LAMPHOLDER	G9 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	I
SHADE	GL192
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB07




Product Notes:

- 1) Lamps not included with light fixture.
- 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances.
- 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions.
- 4) Cable/Chain can be shortened during installation.
- 5) Longer Cable/Chain available on request.
- 6) Additional colour finishes available on request.
- 7.) Dimensions do not include lamps.
- 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Glass	Fixing Bracket MLWB07
HEIGHT	40cm 15.75"	
WIDTH DIAMETER	11cm 4.33"	
LENGTH PROJECTION	8cm 3.15"	
WEIGHT	0.65KG	
LAMPHOLDER	G9 x 1	
MAX WATTAGE	6.5W x 1	
VOLTAGE	220/240v	
IP RATING	44	
CLASS PROTECTION	I	
SHADE	GL192	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	




Product Notes:

- 1) Lamps not included with light fixture.
- 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances.
- 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions.
- 4) Cable/Chain can be shortened during installation.
- 5) Longer Cable/Chain available on request.
- 6) Additional colour finishes available on request.
- 7.) Dimensions do not include lamps.
- 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Glass
HEIGHT	40cm 15.75"
WIDTH DIAMETER	11cm 4.33"
LENGTH PROJECTION	8cm 3.15"
WEIGHT	0.65KG
LAMPHOLDER	G9 x 1
MAX WATTAGE	6.5W x 1
VOLTAGE	220/240v
IP RATING	44
CLASS PROTECTION	I
SHADE	GL192
FLEX BAR CHAIN LENGT	n/a
CABLE TYPE	-

Fixing Bracket MLWB07



Product Notes:

- 1) Lamps not included with light fixture.
- 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances.
- 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions.
- 4) Cable/Chain can be shortened during installation.
- 5) Longer Cable/Chain available on request.
- 6) Additional colour finishes available on request.
- 7.) Dimensions do not include lamps.
- 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.