


BATA Bathroom Light

MLBWL160PCBRZOP

Bronze



MATERIAL	Brass Steel Acrylic
HEIGHT	35cm 13.78"
WIDTH DIAMETER	8cm 3.15"
LENGTH PROJECTION	8cm 3.15"
WEIGHT	1.2KG 2.65lbs
LAMP HOLDER	G9
MAX WATTAGE	6.5W x 2
VOLTAGE	220/240v or 110/120v *
IP RATING	65
CLASS PROTECTION	I
SHADE CODE	GL178 x 2
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	MLCA009

Fixing Bracket -

* Fixing bracket may differ for UL wired products.


Product Notes:

1) Bulbs not included. 2) Dimensions do not include bulbs. 3) All products are individually made-to-order and therefore may differ slightly within manufacturing tolerances. 4) Cable / chain can be shortened during installation. Longer cable / chain lengths available on request. 5) Additional colour finishes may be available on request. 6) UL wired products operate at 110/120v with the appropriate lamp holder. 7) Twisted cable is not available for UL wired products. Round cable in black or brown only is supplied instead. 8) Refer to our website for a full list of terms and conditions.

BATA Bathroom Light

MLBWL160PCMBKOP

Matt Black



MATERIAL	Brass Steel Acrylic
HEIGHT	35cm 13.78"
WIDTH DIAMETER	8cm 3.15"
LENGTH PROJECTION	8cm 3.15"
WEIGHT	1.2KG 2.65lbs
LAMP HOLDER	G9
MAX WATTAGE	6.5W x 2
VOLTAGE	220/240v or 110/120v *
IP RATING	65
CLASS PROTECTION	I
SHADE CODE	GL178 x 2
CABLE CHAIN BAR LENGT	n/a
CABLE TYPE	MLCA009

Fixing Bracket -

* Fixing bracket may differ for UL wired products.

Product Notes:

1) Bulbs not included. 2) Dimensions do not include bulbs. 3) All products are individually made-to-order and therefore may differ slightly within manufacturing tolerances. 4) Cable / chain can be shortened during installation. Longer cable / chain lengths available on request. 5) Additional colour finishes may be available on request. 6) UL wired products operate at 110/120v with the appropriate lamp holder. 7) Twisted cable is not available for UL wired products. Round cable in black or brown only is supplied instead. 8) Refer to our website for a full list of terms and conditions.