



MATERIAL	Brass Plastic Glass	Fixing Bracket -
HEIGHT	12.6cm 4.96"	
WIDTH DIAMETER	27.1cm 10.67"	
LENGTH PROJECTION	1.7cm 0.67"	
WEIGHT	1.86KG 4.1lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	54	
CLASS PROTECTION	I	
SHADE	-	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	

Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Plastic Glass	Fixing Bracket -
HEIGHT	12.6cm 4.96"	
WIDTH DIAMETER	27.1cm 10.67"	
LENGTH PROJECTION	1.7cm 0.67"	
WEIGHT	1.86KG 4.1lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	54	
CLASS PROTECTION	I	
SHADE	-	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	

Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Plastic Glass	Fixing Bracket -
HEIGHT	12.6cm 4.96"	
WIDTH DIAMETER	27.1cm 10.67"	
LENGTH PROJECTION	1.7cm 0.67"	
WEIGHT	1.86KG 4.1lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	54	
CLASS PROTECTION	I	
SHADE	-	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	

Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Plastic Glass	Fixing Bracket -
HEIGHT	12.6cm 4.96"	
WIDTH DIAMETER	27.1cm 10.67"	
LENGTH PROJECTION	1.7cm 0.67"	
WEIGHT	1.86KG 4.1lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	54	
CLASS PROTECTION	I	
SHADE	-	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	

Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



MATERIAL	Brass Plastic Glass	Fixing Bracket -
HEIGHT	12.6cm 4.96"	
WIDTH DIAMETER	27.1cm 10.67"	
LENGTH PROJECTION	1.7cm 0.67"	
WEIGHT	1.86KG 4.1lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	54	
CLASS PROTECTION	I	
SHADE	-	
FLEX BAR CHAIN LENGT	n/a	
CABLE TYPE	-	

Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.