

## BIXA Ceramic Table Lamp

MLCMTL014ANTBRS    Antique Brass



MATERIAL	Brass	Fixing Bracket -
HEIGHT	14cm   5.51"	
WIDTH   DIAMETER	9.5cm   3.74"	
LENGTH   PROJECTION	n/a	
WEIGHT	0.6KG   1.32lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	20	
CLASS PROTECTION	II	
SHADE	-	
FLEX   BAR   CHAIN LENGT	n/a	
CABLE TYPE	MLCA047   2 Core Round   Brown Braid   PVC	

**Product Notes:**

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.

# BIXA Ceramic Table Lamp

MLCMTL014ANTSLV    Antique Silver



MATERIAL	Brass	Fixing Bracket -
HEIGHT	14cm   5.51"	
WIDTH   DIAMETER	9.5cm   3.74"	
LENGTH   PROJECTION	n/a	
WEIGHT	0.6KG   1.32lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	20	
CLASS PROTECTION	II	
SHADE	-	
FLEX   BAR   CHAIN LENGT	n/a	
CABLE TYPE	MLCA028   2 Core Round   Black Braid   PVC	

## BIXA Ceramic Table Lamp

MLCMTL014PCMBK Matt Black



MATERIAL	Brass	Fixing Bracket -
HEIGHT	14cm   5.51"	
WIDTH   DIAMETER	9.5cm   3.74"	
LENGTH   PROJECTION	n/a	
WEIGHT	0.6KG   1.32lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	20	
CLASS PROTECTION	II	
SHADE	-	
FLEX   BAR   CHAIN LENGT	n/a	
CABLE TYPE	MLCA028   2 Core Round   Black Braid   PVC	

### Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



## BIXA Ceramic Table Lamp

MLCMTL014POLBRS Polished Brass



MATERIAL	Brass	Fixing Bracket -
HEIGHT	14cm   5.51"	
WIDTH   DIAMETER	9.5cm   3.74"	
LENGTH   PROJECTION	n/a	
WEIGHT	0.6KG   1.32lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	20	
CLASS PROTECTION	II	
SHADE	-	
FLEX   BAR   CHAIN LENGT	n/a	
CABLE TYPE	MLCA028   2 Core Round   Black Braid   PVC	



[www.mullanlighting.com](http://www.mullanlighting.com)

#### Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.



# BIXA Ceramic Table Lamp

MLCMTL014SATBRS Satin Brass



MATERIAL	Brass	Fixing Bracket -
HEIGHT	14cm   5.51"	
WIDTH   DIAMETER	9.5cm   3.74"	
LENGTH   PROJECTION	n/a	
WEIGHT	0.6KG   1.32lbs	
LAMPHOLDER	E27 x 1	
MAX WATTAGE	40W x 1	
VOLTAGE	220/240v	
IP RATING	20	
CLASS PROTECTION	II	
SHADE	-	
FLEX   BAR   CHAIN LENGT	n/a	
CABLE TYPE	MLCA028   2 Core Round   Black Braid   PVC	

## Product Notes:

1) Lamps not included with light fixture. 2) All products are individually hand crafted, therefore may differ slightly within manufacturing tolerances. 3) Please refer to: <http://www.mullanlighting.com/terms> for full list of Terms & Conditions. 4) Cable/Chain can be shortened during installation. 5) Longer Cable/Chain available on request. 6) Additional colour finishes available on request. 7.) Dimensions do not include lamps. 8.) Products wired to UL standards will operate at 110/120v with the appropriate lampholders.